Trina Solar



Opening the New 500W+ Module Era

Klaus Hofmeister


Product Marketing Manager

Webinar 04.06.2020




2020





Global energy structure and PV development trends





According to IRENA:

Photovoltaic power will lead the global energy revolution. Global solar capacity will reach 8.5 TW by 2050.

Source:


IRENA Roadmap to 2050

LCOE Trend



The global weighted average LCOE of utility-scale PV plants is estimated to have fallen by 77% between 2010 and 2018.


The LCOE for solar PV is already competitive now compared to all fossil fuel generation sources and will be fully competitive in a few years.




IRENA report 2019 11

Module Power Trend (72 cell module size)
















High Power

Maximum expected power: 500W+.



High Efficiency

Benefit from square mono cells and high-density technology, the efficiency of Vertex can reach up to 21%.





High Reliability

Lower initial & annual degradation.

30-year power warranty.




High Power Generation

Excellent temperature coefficient and low irradiation performance.

5% - 30% of additional power generation brought by the back side.

Integration of Innovative Technologies






The largest wafer size:

Largest silicon ingot technology from semiconductor industry



MBB (Multi-Bus bar):


Multiple bus bars match large size wafer perfectly





Non-destructive cutting

and 1/3 split cell balance V_{oc} and I_{sc} well




High-density encapsulation technology:

Minimized space between cells to improve module efficiency by 0.2-0.3%



Size trend of silicon wafers in semiconductor and PV industry





1/3 split cell balance V_{oc} and I_{sc} well

Dividing the cell into three pieces is the optimized layout.

Parameter	Full cell	Half cell	1/3 cell	1/4 cell
P _{max}	473W	495W	500W	502W
Mono-facial I _{sc}	18.2A	18.2A	12.1A	9.1A
V _{oc}	34.3V	34.3V	51.5V	68.7V
Process risk	Low	Low	Normal	High


I_{sc} too high: Reliability risk


Voc too high: BOS cost increases because of less modules per string



Non-destructive cutting (NDC)

Benefit from Non-destructive cutting technology, the cell can be designed to have three uniform pieces.






Section after traditional cutting




Section after Non-destructive cutting



MBB technology






© 2019 Trina Solar. All pi

Trinasolar


Technical Characteristics 5

High-density cell interconnect technology



Value to the PV System






^{*} Based on sample projects in Spain

Improved Power Warranty





PV System Compatibility








Compatible with mainstream inverters.

Compatible with mainstream trackers.











2020 Q3 mass production



Capacity will reach more than 5GW by the end of 2020





500W+ high power with 21% high efficiency







Get in touch

Europe@trinasolar.com

Asia-Pacific APMEA@trinasolar.com

Middle East & Africa
MiddleEast_Africa@trinasolar.com

North America
Jason.Lehrbaum@trinasolar.com





Power beyond Solar

www.trinasolar.com